

PGDQ2.MH15866 - Marking and Labeling Systems - Component

Marking and Labeling Systems - Component

See General Information for Marking and Labeling Systems - Component

SYTEK ENTERPRISES INC

MH15866

UNIT 100
55 GOSTICK PL
NORTH VANCOUVER, BC V7M 3N2 CANADA

Model No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
Pressure-sensitive printed labels.						
SY-002						
	Alkyd paint	100	-40	X	X	-
	Aluminum	100	-40	X	X	-
	Galvanized steel	100	-40	X	X	-
	Polycarbonate	100	-40	X	-	-
	Porcelain	100	-40	X	X	-
	Stainless steel	100	-40	X	X	-
	Acrylonitrile butadiene styrene	80	-40	X	X	-
	Nylon - Polyamide	80	-40	X	X	-
	Polyphenylene oxide/ether	80	-40	X	X	-
SY-003						
	Acrylic paint	150	-40	X	X	-
	Alkyd paint	150	-40	X	X	-
	Aluminum	150	-40	X	X	-
	Epoxy paint	150	-40	X	X	-
	Galvanized steel	150	-40	X	X	-
	Polyester paint	150	-40	X	X	-
	Porcelain	150	-40	X	X	-

	Stainless steel	150	-40	X	X	-
	Nylon - Polyamide	100	-	X	X	-
	Phenolic - Phenol Formaldehyde	100	-	X	X	-
	Polycarbonate	100	-	X	X	-
	Polyphenylene oxide/ether	80	-40	X	X	-
	Polypropylene	80	-	X	X	-
	Polystyrene	80	-40	X	X	-
	Acrylonitrile butadiene styrene	60	-40	X	X	-
SY-004						
	Aluminum	150	-40	X	X	-
	Galvanized steel	150	-40	X	X	-
	Porcelain	150	-40	X	X	-
	Stainless steel	150	-40	X	X	-
	Alkyd paint	100	-40	X	X	-
	Polycarbonate	100	-40	X	X	-
	Acrylonitrile butadiene styrene	80	-40	X	X	-
	Polyphenylene oxide/ether	80	-40	X	X	-
SY-005						
	Alkyd paint	100	-	X	-	-
	Aluminum	100	-	X	-	-
	Epoxy/Polyester powder paint	100	-	X	-	-
	Galvanized steel	100	-	X	-	-
	Nylon - Polyamide	100	-	X	-	-
	Polycarbonate	100	-	X	-	-
	Porcelain	100	-	X	-	-
	Stainless steel	100	-	X	-	-
	Acrylonitrile butadiene styrene	80	-	X	-	-
	Polyphenylene oxide/ether	80	-	X	-	-
	Polypropylene	80	-	X	-	-
	Polystyrene	80	-	X	-	-

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

Marking: Company name and model designation.

Last Updated on 2016-04-25

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2022 UL LLC."